

PROTECTION BOARDS


Expanded Polystyrene Insulation.

R-Shield® expanded polystyrene Protection Boards are economical, light weight and easy to install over foundation walls that have been dampproofed or waterproofed with coatings/membranes.

Installed prior to backfilling, R-Shield Protection Boards provide impact puncture protection for foundation wall coatings/membranes from rocks and potential construction debris in backfill soil. Protection is also provided against crushed stone/gravel used in many foundation drainage designs.

- R-value that never changes and is stable over time
- Range of compressive strengths available
- Closed cell insulation with superior moisture resistance
- High drying potential to rapidly release absorbed moisture
- Meets code requirements for continuous insulation

Strength/R-value.

	Compressive Strength ¹ , psi	R-value/inch ²	
		75°F ³	40°F ⁴
100	10	3.9	4.2
130	13	3.9	4.3
150	15	4.2	4.6
250	25	4.4	4.8

¹ Compressive strength @ 10% deformation.

² R-value units are °F-ft²-h/Btu.

³ Recommended for design in WARM climates.

⁴ Recommended for design in COLD climates.


Proven to meet, or exceed, building codes.

R-Shield is manufactured under an industry leading quality control program monitored by UL and further recognized in UL Evaluation Report UL ER40361-01 and ICC ESR-4743. R-Shield meets ASTM C578, "Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation".



Protection.

R-Shield Protection Boards are available in a range of thicknesses up to 4" and types to assure optimum protection against potential larger stones and construction debris, and for deep fill foundations.



FOAM FACTS:

R-Shield outperforms XPS.

- R-Shield provides a stable long-term R-value at a lower cost
- R-Shield uses a blowing agent with 10 x lower global warming potential and 10,000 x lower ozone depletion
- R-Shield meets strength requirements at a lower cost
- R-Shield and XPS have resistance to moisture, but R-Shield has a higher vapor permeance leading to superior drying potential
- R-Shield with termite treatment available to provide termite resistance

Performance Value.

When you consider all performance characteristics and cost, R-Shield is your best choice for foam insulation.

R-Shield has air in its closed cells and therefore has a stable R-value. Many other insulations use blowing agents that cause R-value loss and are harmful to the environment.

R-Shield has compressive strength to meet specific project requirements.

R-Shield is manufactured to resist moisture absorption in wetting conditions and release absorbed moisture quickly during drying periods, which means R-Shield maintains R-value.

Termite Resistant.

One of the most destructive forces anywhere is termites. R-Shield can be manufactured with a proven and safe additive, that effectively resists termites.

R-Shield is treated to meet ICC ES AC239, "Acceptance Criteria for Termite-Resistant Foam Plastics".

Recyclable.

After it's life as a building insulation, R-Shield is 100% recyclable. It can be ground into granules and reincorporated into new R-Shield products or it can be thermally processed into a resin that's used to manufacture other new products.

Ready to take control? Start here.

If you're ready to have R-Shield contribute to your next project, just contact your Premier Building Systems Technical Sales Representative. They will be happy to give you design consultation, information about R-Shield products, pricing, and answers to all of your questions.

A PRODUCT OF
PREMIER
BUILDING SYSTEMS



www.rshieldinsulation.com | 800-766-3626

Copyright © 2022. R-Shield is a registered trademark of Premier Building Systems. RSI 39 08/22